

## Manual, Assembly instruction: Brodit 719300

With 2 USB-A ports: QC 3.0A + 2.4A. With tilt swivel. 12/24 Volt. 5/7.5/10/15W wireless charging. Adjustable holder. Fits for devices with and without skin with the following dimensions: Width: 61-83 mm, Thickness: 6-11 mm.



**Please read all of the instructions and look at the pictures before attaching the holder.**

1. To adjust the holder for your device: Loosen the screws on the front side of the holder, so the sides of the holders can be adjusted. Place the device in the holder and press the sides together so the device is firmly in place. Tighten the screws on the front side of the holder. 2. Loosen the screw in the center of the mount so you can remove the tilt swivel attaching plate on the back. Place the attaching plate on desired position. Screw the attaching plate into place with the enclosed screws. Place the mount over the attaching plate so the tilt swivel fits. Screw the mount onto the attaching plate. 3. Place the device over the adapter mount and press it straight downward so it slides into place. In order to remove it, press it straight upward and slide it out from the adapter mount. 4. The holder is in place. **IMPORTANT NOTE:** To ensure your holder works in fast charging modes the cable that connects the holder to the power supply should always be connected to the Green USB-A port on the power supply unit (Output: 1). The White USB-A charging port (Output: 2) is spare and can be used to charge secondary devices such as mobile phones / navigation units. The USB ports found in vehicles only provide a 5 Vdc power output, but the Qualcomm power supply that is included is designed to provide 5 Vdc / 9 Vdc / 12Vdc Outputs to support the 7.5W / 10W / 15W fast-charging modes. We do not recommend connecting the wireless charging holder directly to the vehicles USB power supply because it will only provide 5W charging. This is a 15W fast charging holder. Fast charging is device dependent.